

JET-LUBE 5000™

WATER BASED CLEANER AND DEGREASER

DESCRIPTION

JET-LUBE 5000™ is a water based cleaner degreaser that uniquely combines nonhazardous cleaning agents with newly developed emulsifying technology to provide a product that can effectively remove carbon, grease, oil and other organic deposits while being both environmentally safe and ozone friendly. **JET-LUBE 5000 is tomorrow's answer to today's cleaning problems-totally effective yet safe for our environment and atmosphere.** Use full strength for maximum results in shortest time.

Biodegradable	Noncaustic	Noncombustible
Noncorrosive	Nonflammable	Nonfuming
Nontoxic	pH Balanced	Water Soluble
NSF Registered		

JET-LUBE 5000 contains no 1:1:1 Trichloroethane, Fluorocarbons or SARA Title III, Section 313, Part 372 listed ingredients and contains no acids, alkalis, chlorides, ethylene glycol ethers, phosphates of TTO's (Total Toxic Organic Compounds). EPA 624 and 625 test results are available upon request.

JET-LUBE 5000 is the safest and most effective cleaner/degreaser available and can be used for heavy duty parts degreasing, pressure washing, steam cleaning, ultrasound cleaning or simply by brushing or spraying and then rinsing with water or wiping clean. JET-LUBE 5000 is safe on all metal parts and most plastics.

APPLICATIONS

Automotive	Food Processing	Metal Fabrication
Aviation	Industrial	Residential
Electronics	Marine	Utilities

DILUTION RATIOS

JET-LUBE 5000 may be diluted with ordinary tap water or salt water (with reduced affect). Dilution ratios will vary greatly depending on the amount of buildup, temperature and speed required to complete the job. Suggested dilution ratios of water to JET-LUBE 5000:

<u>DILUTE</u>	<u>EQUIPMENT</u>	<u>CLEANING</u>
J-L 5000 to water 1:4	Dip Tanks	Tools, Parts, Food Process Equipment, Presses, Aviation
1:3 - 5	Parts Washer	Engines, Exhaust Hoods, Fork Lifts, Graffiti, Marine
1:20+	Pressure Washer	Cleaning Parts, Floors and General Purpose
1:20+	Steam Cleaner	Engines, Parts, Etc.
1:10+	Ultrasound	For Cleaning Electrical Parts Etc.
1:25+	Trigger Sprayers, Pumps	General Purpose Cleaning and Facility Maintenance

RINSE AND WIPE DRY - TEST FOR COLOR FASTNESS

PRODUCT CHARACTERISTICS

Specific Gravity	1.0
pH	7-8
Viscosity (Cps)	4.5
Flash Point (PMCC Closed Cup)	None to 212°F
(ASTM D93)	
Auto Ignition Point	None to 500°F
Vapor Pressure @ 20°C)	Composite <.04
Evaporation Rate (Butyl Acetate = 1)	>1
Vapor Density (Air = 1)	>1
Boiling Point	212°F (100°C)
Freezing Point	28°F
Volatile Organic Compounds (VOC)	None
SCAQMD Rules 1171, 1122	

- NSF (A1, B2 & C1) Reg. (#048229) for Federally Inspected Facilities
- Meets or exceeds Boeing D6-17487, Rev. J
- Meets or exceeds Douglas CSD #1, Reissued 3/24/89
- Meets or exceeds AMS 1526B (Aircraft Exteriors)
- Meets or exceeds EPA 624 and 625 requirements

PACKAGING

<u>Code No.</u>	<u>Container Size</u>	<u>Container</u>
71043	16 oz.	Spray Bottle
71033	1 gal.	Jug
71035	5 gal.	Jug
71029	50 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.
4849 HOMESTEAD RD.,
P.O. BOX 21258 (77226-1258)
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-674-7617
FAX: 713-678-4604
E-MAIL: sales@jetlube.com
www.jetlube.com

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL

INDUSTRIAL